



Retort Kit, 20 mL Datasheet

Drilling Fluids Testing/ Retorts Equipment

Taha Kimia Tajhiz Co. ,<u>www.tahakimia.ir</u> , <u>www.oilinst.ir</u>, info@tahakimia.com ,Tel: 66431041, Fax: 66430339 2nd Floor, No 35, Behzadi Dd. End, Before Labafinejad St., Jamalzadeh St., Jomhoori Ave., Tehran

DRILLING FLUIDS EQUIPMENT

For over 30 years OFI Testing Equipment (OFITE) has provided instruments and reagents for testing drilling fluids, well cements, completion fluids, and wastewater. In addition to these product lines we also offer a range of instruments for core analysis. From our manufacturing facility in Houston, TX we provide customers all over the world with quality products and exceptional service.

Our drilling fluids product line includes innovative designs such as the Model 900 Viscometer, which showcases our ability to develop new technology to meet customer and industry demands. We also offer Retorts, Aging Cells, Roller Ovens, Mud Balances, Filter Presses, and all other instruments required to evaluate drilling fluid properties according to API Recommended Practice 13B-1 and 13B-2.

As an independent manufacturer and supplier, OFITE has one priority, our customers.



Retort Kit, 20 mL

The Retort provides a method for measuring the percentage (%) of oil and water, and for estimating both suspended and dissolved solids contained in a sample of water-based or oil-based muds. Knowledge of oil, water, and solid content is fundamental to proper control of mud properties when considering oil/water ratios, rheology, density, filtration, and salinity. Knowledge of solids in drilling fluids is essential to evaluation of viscosity control and solids control equipment.

Electronic temperature control (available on 50 mL and 20 mL sizes) provides more accurate, reliable, and reproducible testing. The digital display shows the current working temperature, so you always know your test conditions.



Standard 20 mL Retort Kit

20 mL Retort Kit with Electronic Temperature Control

Features


- Rugged, stainless steel carrying case
- Ultimate in portability
- Small footprint if used in laboratory
- Includes all accessories necessary to run a test

Standard Retort Kit

Accurate, tamper proof temperature controller

Retort Kit with Electronic Temperature Control

- Improves accuracy and readability
- Digital display
- Provides better reproducibility



Technical Specifications and Requirements

- #165-80 20 mL Retort Kit with Thermostat (115V)
- #165-80-1 20 mL Retort Kit with Thermostat (230V)
- #165-80-2 20 mL Retort Kit, with Electronic Temperature Controller (115V)
- #165-80-3 20 mL Retort Kit, with Electronic Temperature Controller (230V)

Specifications

- Maximum Temperature: 1000°F (537° C)
- Cell Capacity: 20 mL
- Heating Capacity: 500 Watts
- Power Requirement: 115 Volt at 3 Amp or 230 Volt at 1.5 Amp, 50/60 Hz
- Size: 9" × 7" × 12" (23 × 18 × 30 cm)
- Weight: 20 lb (9.07 kg)

Optional

#165-06 20 mL Receiver Tube for Retort, 2 Scales: 0 - $100\% \times 0.1$, 0-20 mL $\times 0.1$ mL, with certificate