



Taha Kimia Tajhiz Co.



Chandler Engineering Co.

# Model 3330 In-Line Viscometer Datasheet

## Cement Testing/ Viscometers and Rheometers Equipment



## Model 3330

### IN-LINE VISCOMETER

A Critical Tool for Stimulation Fluids

The Model 3330 In-Line Viscometer provides real-time on location measurement of fracturing fluids viscosity. It is a rugged instrument designed and manufactured to withstand the rigors encountered within field operations. Using Couette Bob and Rotor geometry, the Model 3330 is a concentric cylinder viscometer that meets all API requirements for viscosity measurements of stimulation fluids used in well servicing.

The Model 3330 is extremely durable and designed to withstand the harsh field conditions encountered by Frac Crews every day. Full real-time viscosity monitoring during pumping operations may now be achieved.

The Model 3330 is a ruggedized version of the 3500 series bench-top viscometer and comes standard with API R1-B1 geometry. This instrument is manufactured to endure the harsh environments in which it is designed to operate. Operating at a fixed shear rate of 511 sec<sup>-1</sup>, the Model 3330 sends a continuous measurement of viscosity and temperature to a Control Treatment Monitoring Vehicle via 4-20 mA signal loops. The instrument also provides a direct readout of the current viscosity within the front panel display. This state of the art instrument is also available with an optional pH probe for monitoring the pH of the fluid.

#### Operational Simplicity

The Model 3330 is designed for ease of operation and sits on the low pressure side of the Blender utilizing a slip stream flow through sample system off the hydration tank. The instrument is quickly disassembled for cleaning after each run and critical components may be replaced with minimal operator intervention.



#### FEATURES

- ✓ Robust Design for Field Operations
- ✓ Easy to Set-Up, Operate, Clean, Maintain & Calibrate
- ✓ Meets API Geometry Standards for Oil field Stimulation fluids
- ✓ Couette Style Geometry
- ✓ Multiple Bob Sizes and Spring Factor Combinations Available
- ✓ Real-Time Outputs of Temperature and Viscosity
- ✓ Real-Time Display of Viscosity
- ✓ Optional Real-Time Output of pH

# Model 3330

## Specifications

Shear Rate: 511 sec<sup>-1</sup>

Measurement Accuracy: ±2.0 cP

Sample Temperature: Ambient

Sample Volume: 250mL

Operating Conditions: 50°F - 140°F

10°C - 60°C

Rotor: R1

Bob: B1

Spring: F1

Additional Bob Size and Spring Factor  
Combinations Available

## Utilities

Power Requirements: 12 VDC 6A 72W

Dimensions (wxdxh): 17 x 15 x 20 in.

43 x 38 x 51 cm

Manufacturer's specifications subject to change  
without notice

## Options

3330-01: Transport Case

3330-02: pH Measurement

P-2838: 100cP Calibration Fluid

R0109.002

**AMETEK**<sup>®</sup>

**CHANDLER ENGINEERING**

2001 North Indianwood Avenue, Broken Arrow, OK 74012

Tel: +1 918-250-7200 • Fax: +1 918-459-0165

e-mail: [chandler.sales@ametek.com](mailto:chandler.sales@ametek.com) • [www.chandlereng.com](http://www.chandlereng.com)

Houston Sales and Services

4903 W. Sam Houston Parkway, N., Suite A-400, Houston, TX 77041

Tel: +1 713-466-4900 • Fax: +1 713-849-1924