



API Filter Press, Bench Mount, with Regulator and Hose Datasheet

Drilling Fluids Testing / Filtration Equipment

Taha Kimia Tajhiz Co. , <u>www.tahakimia.ir</u> , <u>www.oilinst.ir</u> , info@tahakimia.com , Tel: 66431041, Fax: 66430339 2nd Floor, No 35, Behzadi Dd. End, Before Labafinejad St., Jamalzadeh St., Jomhoori Ave., Tehran

DRILLING FLUIDS EQUIPMENT

For over 30 years OFI Testing Equipment (OFITE) has provided instruments and reagents for testing drilling fluids, well cements, completion fluids, and wastewater. In addition to these product lines we also offer a range of instruments for core analysis. From our manufacturing facility in Houston, TX we provide customers all over the world with quality products and exceptional service.

Our drilling fluids product line includes innovative designs such as the Model 900 Viscometer, which showcases our ability to develop new technology to meet customer and industry demands. We also offer Retorts, Aging Cells, Roller Ovens, Mud Balances, Filter Presses, and all other instruments required to evaluate drilling fluid properties according to API Recommended Practice 13B-1 and 13B-2.

As an independent manufacturer and supplier, OFITE has one priority, our customers.



API Filter Press, Bench Mount, with Regulator and Hose

The API Pressure Filter Press provides a quick, easy way to evaluate the filtration properties of a drilling fluid. This instrument consists of a pressure cell, frame, filter medium, graduated cylinder, regulator, and hose. It conforms to API specifications, and is suitable for both field and lab use.



Features

- Stainless steel test cell
- Built-in pressure regulator
- Best suited for laboratory use
- Conforms to API specifications
- For Nitrogen and CO, Pressurization
- Nitrogen Tank not included



OFI TESTING EQUIPMENT, INC. 11302 Steeplecrest Dr. Houston, TX 77065 877.837.8683 www.ofite.com *Copyright OFITE 2015

Technical Specifications and Requirements

#140-31 API Filter Press, Bench Mount, with Regulator and Hose

Specifications

•

- Working Pressure: 100 PSI (689.5 kPa)
- Working Temperature: Ambient
- Filtration Area: 7.1 ± 0.1 in² (4,580 ± 60 mm²)
- Working Volume: 400 mL

Optional



#155-20 - Interval Timer



#170-37 - Nitrogen Cylinder